



| Genset | |
|-----------------|----------------|
| Model | JHW-2200GF |
| Voltage | 480/277V |
| Frequency&Speed | 60HZ 1800RPM |
| Prime Power | NA/NA |
| Standby Power | 2430kW/3038kVA |

- **Engine: Baudouin 12M55D2700E311**
- **Alternator: Stamford/Leroy Somer /Hengsheng**
- **Controller: DeepSea/SmartGen /DEIF/ComAp**

General Engine Data

| 转速 Speed | 发动机功率 Gross Engine Output | | |
|-------------|------------------------------|-------------------|-------------------|
| | 持续功率 kW COP kW | 常用功率 kW PRP kW | 备用功率 kW ESP kW |
| 1800r/min | / | / | 2700 |

发动机类型 Engine Type 柴油机 Diesel Engine
 气缸/气门数量 N° of Cylinders / Valves 12/48
 气缸分布型式 Cylinders arrangement V型 V-Type
 缸径×行程 (mm) Bore x Stroke (mm) 180×215
 排量(L) Displacement(L) 65.65
 燃油系统型式 Fuel System .. 电控高压共轨 Electronically controlled high pressure common rail
 进气形式 Aspiration 增压中冷 Turbocharging and intercooling
 压缩比 Compression ratio 16.5
 飞轮壳尺寸 Flywheel housing SAE00
 飞轮尺寸 Flywheel 21"
 飞轮齿圈齿数 N° of teeth on flywheel ring gear 202
 飞轮转动惯量 (kg/m²) Inertia of flywheel (kg/m²) 20.78
 曲轴转动惯量 (kg/m²) Inertia of crankshaft (kg/m²) 16.16
 排放阶段 Emission standard 无排放 Non
 发动机尺寸(长×宽×高) Overall Dimensions without radiator (L x W x H) (mm)
 2957×1544×2305 (以外形图为准 The outer chart shall prevail)
 发动机干重 (kg) Engine dry weight (kg) 9550
 不带辅助启动装置时最低冷启动温度 (°C) Min.cold start temperature without auxiliary starting
 device(°C) -10
 带辅助启动装置时最低冷启动温度 (°C) Min. cold start temperature with auxiliary starting device (°C)
 /
 包装尺寸(长×宽×高) Packing size (L x W x H) (mm) 3720×2002×2557
 运输重量 Packaging quality(kg) 10500

| | |
|--|---------|
| 油底壳机油最小/最大容量 (L) Oil capacity Low / High (L)..... | 330/380 |
| 怠速时机油压力 (kPa) Oil pressure in normal condition idle speed (kPa)..... | ≥180 |
| 在额定转速下的机油压力 (kPa) Oil pressure in normal condition at rated speed..... | 400-650 |
| 机油压力低报警值(kPa) Lowest oil pressure alarm value (kPa) | 180 |
| 机油压力低停机值(kPa) Lowest oil pressure shutdown value (kPa)..... | 150 |
| 额定工况主油道内机油温度范围 The oil temperature range of the main oil passage under rated working condition (°C) | 85~105 |
| 机油流量 (L/min) Oil flow (L/min) | 1315 |
| 额定工况机油燃油消耗比 Oil fuel consumption ratio based on engine fuel consumption data under rated working condition | ≤0.25% |
| 喷油泵进油口最大进油阻力 (kPa) Max. restriction at fuel pump inlet (kPa) | 10 |
| 喷油泵最大回油阻力 (kPa) Max. fuel return restriction (kPa) | 20 |
| 燃油最高进油温度 (°C) Max. fuel inlet temperature (°C)..... | 70 |
| 供油流量 (kg/h) Fuel supply flow (kg/h)..... | 549.06 |
| 输油泵最小压力 (kPa) Min. pressure of fuel pump (kPa)..... | 50 |
| 燃油进油管最小直径 (mm) Min. diameter of inlet pipe (mm)..... | 19 |
| 燃油回油管最小直径 (mm) Min. diameter of return pipe (mm) | 19 |
| 电气系统电压 (负极接地) (V) Electrical system voltage (negative to ground) (V) | 24 |
| 起动机功率(kW) Starter power (kW) | 2×10 |
| 充电发电机额定电流 (A) Battery charger current (A)..... | 55 |
| 启动回路最大电阻 (mΩ) Max. electric resistance of starting circuit (mΩ)..... | 8 |
| 启动回路导线最小截面积(mm ²) Min. sectional area of wire (mm ²) | 70 |
| 加热格栅工作电压(V)/电流(A) Heat The Grille Voltage(V)/Current(A) | / |
| 发动机噪声 (声功率级) (dB(A)) Diesel engine noise (Acoustic power level) (dB(A)) | 125.53 |

Alternator

| | | |
|---|---|---|
| Pole No. | 4-Pole | |
| Exciter Type | Single bearing, Brushless, Self-excited | ✧ NEMAMG1.JIANGHAO,and ANSI standards compliance for temperature rise and motor starting. |
| Power factor | 0.8 | |
| Voltage adjust range | ≅ 5% | ✧ Sustained short-circuit current of up to 300% of the rated current for up to 10 seconds. |
| Insulation Grade | H | |
| Protection Grade | IP23/22 | |
| Phase / wire | 3 phase 4 wires | ✧ Sustained short-circuit current enabling down stream circuit breakers to trip without collapsing the generator field. |
| ✧ Superior voltage waveform from two-thirds Pitch windings and skewed stator. | | |
| ✧ Digital solid-state.volts-per-hertz voltage Regulator with +1% no-load to full-load regulation. | | ✧ Self-ventilated and dripproof construction. |

Control Panel



The control module gives digital readouts of:

- Generator voltage;
- Output frequency;
- Engine speed;
- Battery voltage;
- Engine hours run.



Dimension:6800*2500*2600mm

Weight:15500kg

Fuel Tank:1000-3000L

The **control panel** is an Digital Control Module suitable for a wide variety of single, diesel or gas, gen-set applications.

Monitoring an extensive number of engine parameters, the module will display warnings, shutdown and engine status information on the back-lit LCD screen and illuminated LEDs.

The control module has indicators for failure information:

- Over speed/Low speed,
- Emergency stop
- Low oil pressure;
- High water temperature
- Failure to start
- Battery charger failure

Automatic shutdown occurs under:

- Low engine oil pressure;
- High engine water temperature;
- Over speed/Low speed;
- Failure to start after three attempts.

Electrical system

- Maintenance-free and anti-explosion battery
- Standard breaker
- ABB breaker (optional)
- ATS (optional)
- Battery charger (optional)
- GMS monitoring (optional)

Packing

- Wrapping film packaging
- Tray packaging
- plywood box packaging

Jiangsu Jianghao Generator Co.,Ltd

Address: No.1 Xixu Road, Medical High-tech Zone,
Taizhou city, Jiangsu, China

Contact Person: Anthony Feng

Email: jhfsale@jhgenerator.com

WhatsApp: +86 18652649673

